



**TRUE FOOD SERVICE  
EQUIPMENT, INC.**

2001 East Terra Lane • O'Fallon, Missouri 63366  
(636)240-2400 • Fax (636)272-2408 • (800)325-6152 • Intl Fax# (001)636-272-7546  
Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truefmfg.com

Project Name: \_\_\_\_\_

Location: \_\_\_\_\_

Item #: \_\_\_\_\_ Qty: \_\_\_\_\_

Model #: \_\_\_\_\_

A/A #

S/S #

Model:  
**TR2R-2HG/2HS**

**TR Spec Series:**  
*Reach-In Combination Half Swing Door Refrigerator*



**TR2R-2HG/2HS**

- ▶ Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs and exceptional food safety.
- ▶ Oversized, factory balanced, refrigeration system holds 33°F to 38°F (5°C to 3.3°C) for the best in food preservation.
- ▶ 300 series stainless steel exterior and interior. The very finest stainless with higher tensile strength for fewer dents and scratches.
- ▶ 300 series stainless steel solid door(s). Energy efficient "Low-E", double pane thermal glass door assembly (assemblies) with extruded aluminum frame(s).
- ▶ Patented integrated door light (IDL) system.
- ▶ Equipped with one (1) interior kit option per full section standard, factory installed. Four (4) different interior kits available.
- ▶ Positive seal self-closing door(s) with 120° stay open feature. Lifetime guaranteed door hinges.
- ▶ Entire cabinet structure and solid doors are foamed-in-place using Ecomate. A new, innovative, high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

**ROUGH-IN DATA**

Specifications subject to change without notice.  
Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Cabinet Dimensions (inches) (mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (total ft.) (total m)	Crated Weight (lbs.) (kg)
		L	D†	H*						
TR2R-2HG/2HS	4	51 3/8 1305	34 7/8 886	78 1/4 1988	1/2	115/60/1	10.0	5-15P	9 2.74	660 300

† Depth does not include 1 3/8" (35 mm) for glass door handles.

\*Height does not include 5" (127 mm) for castors, 6" (153 mm) for optional legs and 1" (26 mm) for system mechanical components.



**APPROVALS:**

**AVAILABLE AT:**

Printed in U.S.A.

