

# Beer Dispensers & Club Top

Underbar Equipment  
Beer Dispensers

## **NEW** Direct Draw Beer Dispensers & Club Top Models



\* Does not include keg couplers.

### FEATURES / BENEFITS

- EFFICIENT REFRIGERATION SYSTEM**  
 Turbo Air refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.
- FORCED AIR COOLING SYSTEM**  
 Fast cooling and balanced temperature throughout the cabinet.
- STAINLESS STEEL CABINET CONSTRUCTION**  
 This model boasts a stainless steel interior and exterior (except SB models). It guarantees the utmost in cleanliness and long product life. The Beer Dispenser can add a touch of style to the most refined setting.
- HIGH-DENSITY POLYURETHANE INSULATION**  
 Entire cabinet structure is formed-in-place using high density, CFC free polyurethane insulation.
- CLUB TOP (TCB) MODELS PROVIDE EASY ACCESS TO THE INTERIOR AREA**  
 Club Top is a combined functional cabinet of direct draw cold beer dispenser and glass chiller. This convenient model provides easy access to interior storage area of the refrigerator for chilled beer glasses.
- 3" DIAMETER STAINLESS STEEL INSULATED BEER COLUMNS**
- ERGONOMICALLY DESIGNED DOORS**  
 Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.
- SIDE MOUNT COMPRESSOR UNIT**  
 Through positioning the compressor to the side, the refrigerator can be serviced without being moved. By innovatively creating a **front breathing** feature, this model can provide high efficiency in narrow spaces.
- INCANDESCENT INTERIOR LIGHTING**
- REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN BEVERAGE PRESERVATION**

Model	Swing Door	1/2 Barrels	HP	AMPS	Crated Weight	L D H
TBD-1SD/SB	1	1	1/4	4	185	23 1/2 x 29 1/8 x 37
TBD-2SD/SB	2	2	1/3	7	303/313	58 3/4 x 27 1/8 x 37
TBD-3SD/SB	2	3	1/3	7	338/348	69 1/8 x 27 1/8 x 37
TBD-4SD/SB	2	4	1/2	9	435	90 3/8 x 27 1/4 x 37
TCB-2SD/SB	2	2	1/4	5	333/345	58 7/8 x 27 1/4 x 37 1/8
TCB-3SD/SB	2	3	1/3	7	368/375	69 x 27 1/4 x 37 1/8
TCB-4SD/SB	2	4	1/2	9	480	90 3/8 x 27 1/4 x 37 1/8

\* Height does not include 6" for caster height. \* Height does not include 15-1/4" for draft arm. \* Depth does not include 2" for cap catcher or 1-1/4" for rear spacers.



# TBD/TCB MODELS SPECIFICATIONS

MODEL	TBD-1SD/SB	TBD-2SD/SB	TBD-3SD/SB	TBD-4SD/SB
Exterior Dimension (LxDxH)	23 <sup>1</sup> / <sub>2</sub> x29 <sup>1</sup> / <sub>8</sub> x37	58 <sup>3</sup> / <sub>4</sub> x27 <sup>1</sup> / <sub>8</sub> x37	69 <sup>1</sup> / <sub>8</sub> x27 <sup>1</sup> / <sub>8</sub> x37	90 <sup>3</sup> / <sub>8</sub> x27 <sup>1</sup> / <sub>4</sub> x37
1/2 Barrels	1	2	3	4
Voltage Ⓢ <sub>NEMA-5-15P</sub>	Ⓢ 115/60/1	Ⓢ 115/60/1	Ⓢ 115V/60/1	Ⓢ 115/60/1
Amp	4	7	7	9
Compressor (HP)	1/4	1/3	1/3	1/2
Net Weight	175 lbs	276 lbs	298 lbs	420 lbs
Cord Length (ft)	9	9	9	9
Plug-In	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P

  

MODEL	TCB-2SD/SB	TCB-3SD/SB	TCB-4SD/SB
Exterior Dimension (LxDxH)	58 <sup>7</sup> / <sub>8</sub> x27 <sup>1</sup> / <sub>4</sub> x37 <sup>1</sup> / <sub>8</sub>	69x27 <sup>1</sup> / <sub>4</sub> x37 <sup>1</sup> / <sub>8</sub>	90 <sup>3</sup> / <sub>8</sub> x27 <sup>1</sup> / <sub>4</sub> x37 <sup>1</sup> / <sub>8</sub>
1/2 Barrels	2	3	4
Voltage Ⓢ <sub>NEMA-5-15P</sub>	Ⓢ 115/60/1	Ⓢ 115/60/1	Ⓢ 115/60/1
Amp	5	7	9
Compressor (HP)	1/4	1/3	1/2
Net Weight	335 lbs	355 lbs	425 lbs
Cord Length (ft)	9	9	9
Plug-In	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P

\*Design and specifications subject to change without notice.

- **WARRANTY :** 1 Year Labor and Parts Warranty  
(SB Model) Additional 4 Years Warranty on Compressor
- **WARRANTY :** 2 Years Labor and Parts Warranty  
(SD Model) Additional 3 Years Warranty on Compressor
- **SELF CONTAINED SYSTEM**
- **3.5" CASTERS STANDARD**
- **DOOR LOCKS STANDARD**

(unit : inch)

