

# Glass Door Freezers

Digitally Controlled Uniform Temperature



TGF-23F



TGF-49F

■ **HIGH-TECH MONITOR**

The monitor digitally displays the present temperature, evaporator fan status and the door if open. Alarm sounds when door is opened for more than 30 seconds. You can easily adjust the temperature by pressing the button up or down.

■ **HARDWARE, INSULATION AND CONSTRUCTION**

Provided with casters for easy movement. Our products maintain a constant temperature throughout the unit, even when stocked. Inside temperature is controlled automatically. All refrigeration systems are on slide out rails to make maintenance and service easier. Cabinet body is insulated with 100% foamed-in-place polyurethane foam insulation.

■ **STANDARD FEATURES**

- White color cabinet
- White color frame of door
- Triple pane heated glass door
- Fully adjustable wire shelves with non-corrosive coating
- Fluorescent light for interior display and advertising effect
- Refrigeration system on slide out rail.
- 4" swivel casters

\* A certificated member of NMSDC

\* CEC. California Energy Commission Certificated

\* MEA. City of New York Building Department Approved

■ **DOOR SYSTEM**

To prevent condensation, a transparent triple pane heated glass is used. The door comes with self closing and stay open functions.

■ **STANDARD BACKGUARD IMPROVES AIRFLOW**

■ **SHELVING**

The fully adjustable wire shelves are made of heavy gauge metal wire with non-corrosive coating.

■ **OPTION**

Customized graphics & colors available in quantity.

■ **HOLDS -15°F ~ 5°F**

■ **FOAMED WITH POLYURETHANE, HIGH-DENSITY CELL INSULATION (CFC FREE)**



Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H
TGF-23F	1	23	4	3/4	8.2	375.9	27.0 x 31.0 x 83.8
TGF-49F	2	49	8	1-1/2	11.0	700	54.4 x 31.0 x 83.8
TGF-72F	3	72	12	1-1/2	13.0	985	81.9 x 31.0 x 83.8

\* TGF-72F requires dual voltage 115/208-230V(NEMA L14-20)