Direct Draw Beer Dispenser - 27" Depth Series

- Durable stainless steel top, interior walls, floor and ceiling.
- Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
- **Refrigeration system** keeps the drinks at safe temperatures between $33^{\circ}F$ and $41^{\circ}F$ ($0.5^{\circ}C$ to $5^{\circ}C$).
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Option of stainless steel exterior available.

- Preinstalled heavy-duty casters with brakes.
 Option of leveling feet available.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- Self-Closing doors with locks.
- LED interior lighting.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- Refrigerant: HYDRO-CARBON R290.



MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH inches mm	CAPACITY cu.ft. barrels	НР	AMPS	VOLTAGE	PLUG TYPE
UDD-1-HC	1	2	23 1/2 x 30 3/8 x 38 3/4	6.5	1/6	1.92	115/60/1	NEMA 5-15P
			596 x 772 x 983	1*1/2	1/0			
UDD-2-HC	2	4	58 7/8 x 27 3/4 x 35 5/8	19	1/5	2.88	115/60/1	NEMA 5-15P
			1495 x 705 x 905	2*1/2	1/3			
UDD-3-HC	2	4	69 1/8 x 27 3/4 x 35 5/8	23.3	1/5	3.6	115/60/1	NEMA 5-15P
			1755 x 705 x 905	3*1/2	1/3			
UDD-4-HC	3	6	90 3/8 x 27 3/4 x 35 5/8	32	1/4+	4.7	115//60/1	NEMA 5-15P
			2295 x 705 x 905	4*1/2	±/ ¬ ·			

^{*} Height does not include 15.8"(402mm) for draft arm.

Specifications subject to change without notice.

Voltage 230-240/50/1 available.

Plug type varies by country.

