



|              |     |          |  |       |
|--------------|-----|----------|--|-------|
| PROJECT NAME |     | LOCATION |  | AIA # |
| ITEM #       | QTY | MODEL #  |  | SIS # |

# SPEC SERIES®

REACH-IN SOLID SWING DOOR FREEZERS

| models | STR2F-2S | STA2F-2S | STG2F-2S |
|--------|----------|----------|----------|
|--------|----------|----------|----------|




| STR2F-2S        |   |
|-----------------|---|
| <b>Exterior</b> | Stainless steel door, front & sides.                                  |
| <b>Interior</b> | Stainless steel side walls, back, floor, door liner, & ceiling.       |
| <b>Shelving</b> | (1) Interior kit option included per full section, factory installed. |

| STA2F-2S        |  |
|-----------------|--|
| <b>Exterior</b> | Stainless steel door, front & sides.                         |
| <b>Interior</b> | Aluminum side walls & back. Stainless steel floor & ceiling. |
| <b>Shelving</b> | (3) Heavy duty, chrome plated, wire shelves per section.     |

| STG2F-2S        |  |
|-----------------|--|
| <b>Exterior</b> | Stainless steel door & front, with matching aluminum sides.  |
| <b>Interior</b> | Aluminum side walls & back. Stainless steel floor & ceiling. |
| <b>Shelving</b> | (3) Heavy duty, PVC coated, wire shelves per section.        |

## plan view



| SPECIFICATIONS  |                                |               |
|---|--------------------------------|---------------|
| Dimensions  | in.                            | mm.           |
| Length  | 52 <sup>5</sup> / <sub>8</sub> | 1337          |
| Depth   | 33 <sup>3</sup> / <sub>4</sub> | 858           |
| Height  | 77 <sup>3</sup> / <sub>4</sub> | 1975          |
| Electrical  | U.S.                           | International |
| Horsepower  | 3/4                            | N/A           |
| Amps  | 8.7                            | N/A           |
| Voltage   | 115/60/1                       |               |
| NEMA  | 5-15P                          |               |
| Cord Length   | 9 ft.                          | 2.74 M.       |
| 115/60/1 NEMA-5-15R<br>* Height does not include 6 <sup>1</sup> / <sub>8</sub> " (156 mm) for castors or 6" (153 mm) for optional legs. Height does not include 1/4" (7mm) for system mechanical components.<br>† Depth does not include 1 1/2 for door handle. |                                |               |

Specifications subject to change without notice. Chart dimensions are rounded up to the nearest 1/8" (millimeters rounded up to the next whole number).



|              |          |         |
|--------------|----------|---------|
| PROJECT NAME | LOCATION | AIA #   |
| ITEM #       | QTY      | MODEL # |
|              |          | SIS #   |

# SPEC SERIES®

REACH-IN SOLID SWING DOOR REFRIGERATOR

|        |          |          |          |
|--------|----------|----------|----------|
| models | STR2F-2S | STA2F-2S | STG2F-2S |
|--------|----------|----------|----------|



## standard features

### REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) R404A refrigerant.
- High capacity, factory balanced refrigeration system that maintains -10°F (-23.3°C) temperatures. Ideal for both frozen foods and ice cream.
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- Top mounted refrigeration system with evaporator positioned out of food zone to maximize capacity.
- Automatic defrost system time-initiated, temperature-terminated. Saves energy consumption and provides shortest possible defrost cycle.
- Automatic evaporator fan motor delay during defrost cycle.

### CABINET CONSTRUCTION

- Insulation - entire cabinet structure and solid door are foamed-in-place using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- 5" (127 mm) diameter plate castors - locks provided on front set.

### DOORS

- Lifetime guaranteed bolt style door locks standard.
- Lifetime guaranteed heavy duty all metal working door handles.
- Positive seal self-closing door with 120° stay open feature. Lifetime guaranteed external cam lift door hinges, four (4) per door section.
- Magnetic door gaskets of one piece construction, removable without tools for ease of cleaning.

### LIGHTING

- LED interior lighting, safety shielded. (STR/STA models standard, STG optional)

### MODEL FEATURES

- Exterior digital temperature display, available with either °F or °C.
- Evaporator epoxy coated to eliminate the potential of corrosion
- Curb mounting ready.
- NSF-7 compliant for open food product.

### ELECTRICAL

- Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.

### OPTIONAL FEATURES/ ACCESSORIES

- (upcharge & lead times may apply)*
- 6" (153 mm) standard legs.
  - 6" (153 mm) seismic/flanged legs.
  - 6" (153 mm) stainless steel legs.
  - Additional shelves.

### SHELVING KIT OPTIONS

- STR series kits factory installed at no charge. STA & STG series kits field installed, upcharge applies, lead times may apply.
- Kit #1: Nine (9) sets of #1 type tray slides and pilasters (field installed), bottom support of one (1) 18"L x 26"D (458 mm x 661 mm) pan or two (2) 14"L x 18"D (356 mm x 458 mm) pans.
- Kit #2: One (1) set half-section #2 steel rod tray slides and pilasters (field installed), rim support of one (1) 18"L x 26"D (458 mm x 661 mm) pan.
- Kit #3: Six (6) sets of universal type tray slides and pilasters (field installed), bottom support of one (1) 18"L x 26"D (458 mm x 661 mm) pan, two (2) 14"L x 18"D (356 mm x 458 mm) pans or two (2) 12"L x 20"D (305 mm x 508 mm) pans.
- Kit #4: Three (3) chrome shelves 25"L x 27 3/4"D (635 mm x 705 mm). Four (4) shelf supports included per shelf (field installed); adjustable on 6" (153 mm) increments. Optional wall mounted shelf support pilasters (field installed) with four (4) shelf clips per shelf available; adjustable on 1/2" (13 mm) increments (must order at time of cabinet order).
- Additional kit option components available individually.

**WARRANTY**  
 One year warranty on all parts and labor and an additional 4 year warranty on compressor. (U.S.A. only)

METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER  
 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

|  |            |           |       |      |    |      |
|--|------------|-----------|-------|------|----|------|
|  | Model      | Elevation | Right | Plan | 3D | Back |
|  | ST( )2F-2S |           |       |      |    |      |