



range		
model	T-50L	T-80L
gross capacity (L)	60L	84L
net capacity (L)	56L	81L
gross weight (kg)	27KG	31KG
net weight (kg)	25KG	29KG
interior dimension (mm)	333×345×508	373×345×653
exterior dimension (mm)	430×465×810	460×460×950
packing dimension (mm)	455×505×885	505×505×1030
20GP/40GP/40HQ	140/295/345	88/184/230
certificates	CE / CB / RoHS	CE / CB / RoHS
climate class	ST	ST
outer finishing	painted steel	painted steel
inner finishing	embossed aluminum	embossed aluminum
body color	white / black	white / black
door frame color	white / black	white / black
shelf (material / No.)	wire, 2 pcs	wire, 2 pcs
wheels	2 adjustable legs	2 adjustable legs
handle	recessed	recessed
glass door	2 layer hollow tempered glass	2 layer hollow tempered glass
water tray	auto-evaporation	auto-evaporation
key/lock	optional	optional
foaming agent	cyclopentane	cyclopentane
refrigerant (g)	R600a	R600a
voltage/frequency	110V/60HZ	110V/60HZ
compressor	Huayi B30H	Huayi B30H
power (W)	120W	120W
energy consumption(kw.h)	0.72KW.h/24h	0.90KW.h/24h
evaporator	roll bond	roll bond
condenser	web type	web type
temp control	mechanical	mechanical
LED light	optional	optional
sticker	optional	optional

Remarks:

Specifications subject to changes without prior notification.