

Universal Manufacturing



Intertek
3029079



Intertek
3029079

- * CONFORMS TO UL STD. 471
- * CERTIFIED TO CSA STD. C22.2 NO.120
- * CONFORMS TO NSF/ANSI STD.7



UGDS54

- **CABINET CONSTRUCTION**
Exterior -Coated steel
Interior - attractive, aluminum liner with stainless steel floor.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
Double pane glass door
Self closing. Positive seal, torsion type closure system.
- **Refrigeration system** holds 33°F to 41°F (0°C to 5°C), Ideal for beverage and soft drinks
- **Electronic control system:**
Adjustable temperature set point and defrost frequency
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Fluorescent or LED lamps**
- **FOAMED-IN-PLACE POLYURETHANE HIGH DENSITY CELL INSULATION (CFC FREE)**

Bottom mounted units feature:

- "No stoop" lower shelf.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

NSF	Model	Doors	Shelves	Cabinet Dimensions (inches)			CAP. CU.FT.	HP	Voltage	Amps	NEMA Config.
				L	D	H					
	G1.2YBM2F	2	8	53.1	31.9	79.3	45	1/2+	115/60/1	9.2	5-15P 