

# Universal Manufacturing



Intertek  
3029079



Intertek  
3029079

- \* CONFORMS TO UL STD. 471
- \* CERTIFIED TO CSA STD. C22.2 NO.120
- \* CONFORMS TO NSF/ANSI STD.7



## Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

NSF	Model	Doors	Shelves	Cabinet Dimensions (inches)			CAP. CU.FT.	HP	Voltage	Amps	NEMA Config.
				L	D	H					
	G768BM2F	2	8	48	25.6	80.3	29	1/2+	115/60/1	10.1	5-15P

## UGDSW48

- **CABINET CONSTRUCTION**  
Exterior - Coated steel  
Interior - attractive, aluminum liner with stainless steel floor.
  - **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
  - **Standard door features:**  
Double pane glass door  
Self closing. Positive seal, torsion type closure system.
  - **Refrigeration system** holds 33°F to 41°F (0°C to 5°C), Ideal for beverage and soft drinks
  - **Electronic control system:**  
Adjustable temperature set point and defrost frequency  
Error codes to diagnose service issues
  - **Shelf:** Adjustable, heavy duty PVC coated shelves.
  - **Fluorescent or LED lamps**
  - **FOAMED-IN-PLACE POLYURETHANE HIGH DENSITY CELL INSULATION (CFC FREE)**
- Bottom mounted units feature:**
- "No stoop" lower shelf.
  - Easily accessible condenser coil for cleaning, and easy service access
  - Simple installation with no plumbing required

