

# Universal Manufacturing



- \* CONFORMS TO UL STD. 471
- \* CERTIFIED TO CSA STD. C22.2 NO.120
- \* CONFORMS TO NSF/ANSI STD.7



## UHBDC72


- **Balanced refrigeration system designed to operate at 36°F ~ 43°F .**
- **Stainless steel floor and walls, standard.**
- **Sliding doors.**
- **12V LED lighting system, safe for users to operate.**
- **Electronic control system:**  
**Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation.**
- **NSF-7 compliant for open food product.**

### Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| NSF | Model    | Doors | Shelves | Cabinet Dimensions<br>(inches)<br>(mm) |        |             | HP   | Voltage  | NEMA Config.  |
|-----|----------|-------|---------|--|--------|-------------|------|----------|---|
|     |          |       |         | L                                      | D      | H           |      |          |   |
|     | CD1800-3 | 2     | 3       | 70 7/8                                 | 28 3/4 | 55 1/8 (in) | 1/2+ | 115/60/1 |  5-15P |