

Universal Manufacturing



* CONFORMS TO UL STD. 471
 * CERTIFIED TO CSA STD. C22.2 NO.120
 * CONFORMS TO NSF/ANSI STD.7



URCD48

- **CABINET CONSTRUCTION**
 Exterior -Coated steel
 Interior - attractive, aluminum liner with stainless steel floor.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
 Low-E, double pane, curved frontal glass
- **Refrigeration system:** Gravity coil refrigeration system provides high humidity environment for meats and deli products, which holds 32°F ~43° F
- **Electronic control system:**
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath

Bottom mounted units feature:

- "No stoop" lower shelf.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

NSF	Model	Doors	Shelves	Cabinet Dimensions (inches)			CAP. CU.FT.	HP	Voltage	Amps	NEMA Config.
				L	D	H					
	DC120	2	6	47.25	32.5	42.88	18	1/3+	115/60/1	5.8	5-15P (2 pcs)