

Model:

CFD-3RRG

Reach-In Refrigerator:

Reach-In Swing Glass Door Refrigerator:



CFD-3RRG

- **Stainless steel exterior** retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
Positive seal self-closing door.
Duralumin door frame
Tempering glass to protect personal safety.
- **Refrigeration system** holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- **Electronic control system:**
Adjustable temperature set point and defrost frequency
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath


Bottom mounted units feature

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Cord Length (total ft.) (total m)	NEMA Config.
			L	D	H					
CFD-3RRG	3	9	80 7/8 2054	32 1/4 818	82 1/2 2095	72 2040	3/4+	115/60/1 230-240/50/1	9 2.74	5-15P 

Plug type varies by country.



GUANGDONG XINGXING REFRIGERATION EQUIPMENT CO.,LTD

Add: Nanfeng Road, Nanbian Industrial Park D1, Leping Town, Sanshui, Foshan, G.D. Province, China

Tel: +86-757-87323900 Fax: +86-757-87323928 E-mail: trade@gdxxingxing.com Website: www.gdxxingxing.com