

Universal Manufacturing



* CONFORMS TO UL STD. 471
 * CERTIFIED TO CSA STD. C22.2 NO.120
 * CONFORMS TO NSF/ANSI STD.7



- **Stainless steel interior and exterior** retains attractive finish longer. Matching aluminium finished back
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:** Positive seal self-closing door(s) with 90° stay open feature. Magnetic door gasket(s) removable without tools for easy of cleaning
- **Refrigeration system** holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- **Electronic control system:** Adjustable temperature set point and defrost frequency
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath
- **Condensing unit** access in back of cabinet, slides out for easy maintenance
- **Insulated lid** on prep units helps maintain food freshness.

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| NSF | Model | Doors | Shelves | Cabinet Dimensions (inches) | | | CAP. CU.FT. LITER | HP | Voltage | Amps | NEMA Config. |
|-----|--------|-------|---------|-----------------------------|----|----|-------------------|------|----------|------|--------------|
| | | | | L | D | H | | | | | |
| | USPT48 | 2 | 2 | 47 | 34 | 46 | 7.8 | 1/3+ | 115/60/1 | 7.8 | 5-15P |

***1 YEARS PARTS AND 5 YEARS COMPRESSOR WARRANTY**