Model:

Solid Door Merchandiser:

G25F-HC

Swing Door Refrigerator



G25F-HC

- CABINET CONSTRUCTION Exterior

 Coated steel

 Interior attractive, aluminum liner with stainless steel floor.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features:
 Double pane white solid door
 Self closing. Positive seal, torsion
 type closure system.
- Refrigeration system holds 33°F to 41°F (0°C to 5°C), Ideal for beverage and soft drinks
- Electronic control system:
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Fluorescent or LED lamps
- FOAMED-IN-PLACE
 POLYURETHANE HIGH DENSITY
 CELL INSULATION (CFC FREE)

Bottom mounted units feature:

- "No stoop" lower shelf.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| | | | Cabinet Dimensions (inches) (mm) | | | CAP. CU.FT. | | | | |
|---------|-------|---------|--|-------------|------------|----------------|------|----------|------|--------------|
| Model | Doors | Shelves | L | D | Н | LITER | HP | Voltage | Amps | NEMA Config. |
| G25F-HC | 1 | 4 | 21.7 550 | 21.7 550 | 63 1600 | 9.1 258 | 1/4+ | 115/60/1 | 5.8 | 5-15P |

Plug type varies by country.



